



PEAKLITE

Miniature List

NO	Shape	Market Designation	Range	V	W	BASE	TEST VOLT	MAX. WATT	LUMENS FLUX
T2301	T6.5			12	2	BA7s	13.5	2.3	10±25%
T2302	T6.5			24	3	BA7s	13.5	2.5	10±25%
T2303	T8.5			12	2	BA9s	28	3	12.5±25%
T2304	T8.5			24	2	BA9s	13.5	3.5	17.5±30%
T2305	T8.5			12	3	BA9s	13.5	4.4	22±30%
T2306	T8.5	T4W		12	4	BA9s	13.5	4.4	35±30%
T2307	T8.5	T4W	LL	12	4	BA9s	13.5	4.4	35±30%
T2308	T8.5	T4W	BL	12	4	BA9s	28	5.5	35±30%
T2309	T8.5	T4W		24	4	BA9s	28	5.5	35±30%
T2310	T8.5	T4W	HD	24	4	BA9s	13.5	26.5	35±30%
S2301	S25	P21W		12	21	BA15s	13.5	26.5	460±15%
S2302	S25	P21W	LL	12	21	BA15s	28	29.7	460±15%
S2303	S25	P21W		24	21	BA15s	28	29.7	460±15%
S2304	S25	P21W	HD	24	21	BA15s	28	29.7	460±15%
S2305	S25	P21W	HD/LL	24	21	BA15s	28	29.7	
S2306	S25	CA		24	21	BA15s	12.8	2.2A	280±20%
S2307	S25	1156		12	32CP	BA15s	12.8	2.2A	32CP±10%
S2308	S25	1156	LL	12	32CP	BA15s	13.5	26.5	32CP±10%
S2309	S25	PY21W		12	21	BAU15s	13.5	26.5	280±20%
S2310	S25	PY21W	LL	12	21	BAU15s	13.5	26.5	280±20%
S2311	S25	PY21W	PA	12	21	BAU15s	28	29.7	280±20%
S2312	S25	PY21W		24	21	BAU15s	28	29.7	280±20%
S2313	S25	PY21W	HD	24	21	BAU15s	13.5	26.5	280±20%
S2314	S25	PR21W		12	21	BAW15s	13.5	26.5/6.6	110±20%
S2315	S25	P21/5W		12	21/5	BAY15d	13.5	26.5/6.6	440±15% / 35±20%
S2316	S25	P21/5W	LL	12	21/5	BAY15d	28	29.68/11	440±15% / 35±20%
S2317	S25	P21/5W		24	21/5	BAY15d	28	29.68/11	440±15% / 40±20%
S2318	S25	P21/5W	HD	24	21/5	BAY15d	28	21.2/11	440±15% / 40±20%
S2319	S25			24	18/5	BAY15d	12.8/14	2.2A/0.637A	320±20% / 40±20%
S2320	S25	1157		12	32/3CP	BAY15d	12.8/14	2.2A/0.637A	32CP±10% / 3CP±12%
S2321	S25	1157	LL	12	32/3CP	BAY15d	12.8/14	2.2A/0.518A	32CP±10% / 3CP±12%
S2322	S25	2057		12	32/2CP	BAY15d	12.8/14	2.2A/0.518A	32CP±10% / 2CP±12%
S2323	S25	2057	LL	12	32/2CP	BAY15d	12.8/14	2.2A/0.637A	32CP±10% / 2CP±12%
S2324	S25	1157NA		12	24/2.2CP	BAY15d	12.8/14	2.2A/0.637A	24CP±30% / 2.2CP±30%
S2325	S25	1157NA	LL	12	24/2.2CP	BAY15d	12.8/14	2.2A/0.518A	24CP±30% / 2.2CP±30%
S2326	S25	2057NA		12	24/1.5CP	BAY15d	12.8/14	2.2A/0.518A	24CP±30% / 1.5CP±30%
S2327	S25	2057NA	LL	12	24/1.5CP	BAY15d	13.5	26.5/5.5	24CP±30% / 1.5CP±30%
S2328	S25	P21/4W		12	21/4	BAZ15d	13.5	26.5/5.5	440±15% / 15±20%
S2329	S25	P21/4W	LL	12	21/4	BAZ15d	28	29.7/8.8	440±15% / 15±20%
S2330	S25	P21/4W		24	21/4	BAZ15d	13.5	26.5	440±15% / 20±20%
T2311	T20	W21W		12	21	W3x16d	13.5	26.5	460±15%
T2312	T20	WY21W		12	21	WX3x16d	13.5	26.5/6.6	280±20%
T2313	T20	W21/5W		12	21/5	W3x16q	12.8	32.1	440±15% / 35±20%
S2331	S8	P27W 3156		12	27	W2.5x16d	12.8	1.728A	475±15%
S2332	S8	3155		12	21CP	W2.5x16d	12.8/14	32.1/8.5	21CP±10%
S2333	S8	P27/7W 3157		12	27/7	W2.5x16q	12.8/14	2.2A/0.518A	475±15% / 36±15%
S2334	S8	3057		12	32/2CP	W2.5x16q	12.8/14	2.2A/0.518A	32CP±10% / 2CP±12%
S2335	S8	3057	LL	12	32/2CP	W2.5x16q	12.8/14	2.2A/0.518A	32CP±10% / 2CP±12%
S2336	S8	3057NA		12	24/1.6CP	W2.5x16q	12.8/14	2.2A/0.518A	24CP±30% / 1.6CP±30%



PEAKLITE

Miniature List

NO	Shape	Market Designation	Range	V	W	BASE	TEST VOLT	MAX. WATT	LUMENS FLUX
S2337	S8	3057NA	LL	12	24/1.6CP	W2.5x16q	12.8/14	2.2A/0.637A	24CP±30% / 1.6CP±30%
S2338	S8	3157	LL	12	32/3CP	W2.5x16q	12.8/14	2.2A/0.637A	32CP±10% / 3CP±12%
S2339	S8	3157NA		12	24/2.2CP	W2.5x16q	12.8/14	2.2A/0.637A	24CP±30% / 2.2CP±30%
S2340	S8	3157NA	LL	12	24/2.2CP	W2.5x16q	12.8/14	32.1/8.5	24CP±30% / 2.2CP±30%
S2341	S8	PY27/7W 3735NA		12	27/7	WX2.5x16q	13.5	5.5	280±15% / 21±15%
T2314	T16	R5W		12	5	BA15s	13.5	5.5	50±20%
T2315	T16	R5W	LL	12	5	BA15s	28	7.7	50±20%
T2316	T16	R5W		24	5	BA15s	28	7.7	50±20%
T2317	T16	R5W	HD	24	5	BA15s	28	7.7	50±20%
T2318	T16	R5W	HD LL	24	5	BA15s	13.5	11	50±20%
T2319	T16	R10W		12	10	BA15s	13.5	11	125±20%
T2320	T16	R10W	LL	12	10	BA15s	13.5	11	125±20%
T2321	T16	R10W		24	10	BA15s	28	14	125±20%
T2322	T16	R10W	HD	24	10	BA15s	28	14	125±20%
T2323	T16	R10W	HD LL	24	10	BA15s	28	14	125±20%
T2324	T16	R5W		12	5	BA15d	13.5	5.5	50±20%
T2325	T16	R5W		24	5	BA15d	28	7.7	50±20%
T2326	T16	R10W		12	10	BA15d	13.5	11	125±20%
T2327	T16	R10W		24	10	BA15d	28	14	125±20%
T2328	T16	RY10W		12	10	BAU15s	13.5	11	75±20%
T2329	T16	RR5W	R	12	5	BAW15s	13.5	5.5	12±25%
T2330	T16	RR10W	R	12	10	BAW15s	13.5	11	30±25%
T2331	T5			12	1.2	W2x4.6d	13.5	1.3	7.5±25%
T2332	T5		FR	12	1.2	W2x4.6d	13.5	1.3	5±25%
T2333	T5	W2.3W		12	2.3	W2x4.6d	13.5	2.5	18.6±20%
T2334	T5			12	3	W2x4.6d	13.5	3.3	22.5±33%
T2335	T5			24	1	W2x4.6d	28	1.2	4±25%
T2336	T5			24	1.2	W2x4.6d	28	1.5	7.5±25%
T2337	T5			24	2	W2x4.6d	28	2.5	15±25%
T2338	T10			12	2	W2.1x9.5d	13.5	2.2	13±30%
T2339	T10			24	2	W2.1x9.5d	28	2.6	13±30%
T2340	T10	W3W		12	3	W2.1x9.5d	13.5	3.3	22±30%
T2341	T10	W3W		24	3	W2.1x9.5d	28	4.6	22±30%
T2342	T10	W5W		12	5	W2.1x9.5d	13.5	5.5	50±20%
T2343	T10	W5W	BL	12	5	W2.1x9.5d	13.5	5.5	50±20%
T2344	T10	WY5W		12	5	W2.1x9.5d	13.5	5.5	30±20%
T2345	T10	W5W		24	5	W2.1x9.5d	28	7.7	50±20%
T2346	T15	W10W		12	10	W2.1x9.5d	13.5	11	125±20%
T2347	T15	W16W		12	16	W2.1x9.5d	13.5	21.4	310±20%
T2348	T15	WY16W		12	16	W2.1x9.5d	13.5	21.4	190±20%