

NO	SPEC	V	W	BASE	E-MARK	TEST VOLT	MAX. WATT	LUMINS FLUX
1121Y	H1	12V	55W	P14.5S	E4	13.2	68	1550±15%
3121Y	H3	12V	55W	PK22S	E4	13.2	68	1450±15%
4121Y	H4	12V	60/55W	P43T	E4	13.2	75/68	1650/1000±15%
7121Y	H7	12V	55W	PX2D	E4	13.2	58	1500±10%
H801Y	H8	12V	35W	PGJ19-1	E4	13.2	43	800±15%
H804Y	H8B	12V	35W	PGJY19-1		13.2	43	800±15%
H901Y	H9	12V	65W	PGJ19-5	E4	13.2	73	2100±10%
H902Y	H9B	12V	65W	PGJY19-5		13.2	73	2100±10%
H11Y	H11	12V	55W	PGJ19-2	E4	13.2	62	1350±10%
H115Y	H11B	12V	55W	PGJY19-2		13.2	62	1350±10%
H101Y	H10	12V	42W	PY20D	E4	13.2	50	850±15%
H131Y	H13 9008	12V	60/55W	P26.4T		13.2	75/68	1700/1100±15%
H151Y	H15	12V	15/55W	PGJ23T-1	E4	13.2	19/64	260/1350±10%
H161Y	H16	12V	19W	PGJ19-3	E4	13.2	26	500+10%/-15%
9465Y	HB1 9004	12V	65/45W	P29t		12.8	70/50	1200/700±15%
9360Y	HB2 9003	12V	60/55	P43t		12.8	72/65	500/910±10%
9560Y	HB3 9005	12V	60E	P20d	E4	13.2	73	1860±12%
9560XS	HB3A 9005XS	12V	60W	P20d		13.2	73	1860±12%
9651Y	HB4 9006	12V	51W	P22d	E4	13.2	62	1095±15%
9651XS	HB4A 9006XS	12V	51W	P22d		13.2	62	1095±15%
9755Y	HB5 9007	12V	65/55W	PX29t		12.8	70/60	1350/1000±15%
9165Y	HIR1 9011	12V	65W	PX20d		13.2	63	2500±15%
9255Y	HIR2 9012	12V	55W	PX20d	E4	13.2	63	1875±15%